

ACRYLOC® INTERIOR PRIMER

PRODUCT TYPE

Exported Products

PACKAGING

5L, 20L Heavy Duty Plastic Pail

NOMINAL WEIGHT6.5kg, 25.5kg

DESCRIPTION

Acryloc® *Interior Primer* is a good quality, Low Odour, Interior Primer, ideal for interior walls and ceilings throughout the home, office or workspace.

Acryloc® *Interior Primer* is easy to apply and fast drying and is suitable for most internal surfaces including, hard plaster, MDF, fibrous-cement sheet, masonry, paper faced plasterboard, softwood & ceilings.

FEATURES & BENEFITS

- Low Odour
 - Excellent adhesion
 - High hiding power
 - Easy to apply, low spatter formula
 - Water based, Easy & safe clean up
 - Can be tinted
-

SUBSTRATE PREPARATION - paint will not adhere to a surface that is dirty.

- Areas not to be coated should be masked and protected

New Unpainted Surfaces

Fill nail holes, cracks and imperfections with an appropriate patching material and sand smooth.

Remove dust and make sure that the surface is clean, sound and free from contaminants such as oil, mould release, silicone, grease and efflorescence.

Previously painted surfaces

Wash down with sugar soap and rinse with clean water.

Check for soundness of the original coating, remove any loose or flaking paint, fill holes and cracks and sand smooth.

Gloss or Semi-Gloss finishes must be completely dulled by sanding.

APPLICATION

- Mix thoroughly and check that the colour (if tinted) is correct before commencing work.

Method

- Apply 1 full even coat of Acryloc *Interior Primer* by brush, spray or roller.
- For Roller application, a medium nap (12mm) roller is recommended; use a larger nap (25mm on rough surfaces). High quality synthetic rollers give best performance. Use a 13 or 15 thou spray tip with Airless spray.

Important Notes

- Care should be taken to keep Acryloc *Interior Primer* off windows and adjacent surfaces that are not to be coated.
- Application should be carried out on a day with temperatures above 10°C and below 32°C.
- Acryloc Interior Primer is not recommended for exterior use.

Clean-Up

- Clean up with water
-

OTHER CONSIDERATIONS**Shelf-Life – Unopened Containers**

Maximum two (2) years from date of manufacture when stored correctly

Transport & Storage

Pails should not be stacked more than three (3) high during transportation and must be transported upright

Store in a cool place, upright, out of direct sunlight and above 4°C

For further information refer to **MSDS** for Acryloc *Interior Primer*

TECHNICAL DATA

APPEARANCE	Viscous white liquid		
ODOUR	Low		
RESIN TYPE	Styrene Acrylic Emulsion		
APPLICATION METHODS	Roller, brush, spray		
SPECIFIC GRAVITY (NOMINAL)	1.28		
VOLUME SOLIDS (APPROX)	29%		
WEIGHT SOLIDS (APPROX)	44%		
THEORETICAL COVERAGE	12-16 m ² /L per coat		
WET FILM THICKNESS (RECOMM)	80-100 microns per coat		
DRY FILM THICKNESS (MIN)	23-29 microns per coat		
DRY TIME (25°C & 50% RH) (APPROX)	Tack Free	Recoat/ Overcoat	Fully Dried
	1 hour	2 hours	48 hours
NO. OF COATS	1 coat is recommended		
GLOSS LEVEL	Flat		
SOLVENT FOR CLEANING	Water		
FLAMMABILITY	Non-flammable		

SAFETY & HANDLING

Refer to **MSDS** for **Acryloc Ultra PSU** before use. For further information on Material Safety Data Sheets, call the Acryloc Tech – Info line on **1300 661 745** or visit **www.acryloc.com.au**

When working with **Acryloc Ultra PSU** observe the usual precautions for handling acrylic water based products including:

- Avoid inhalation of the vapour, prolonged skin contact and particularly eye contact
- Wear protective clothing to minimize skin contact and wear goggles where splatter is likely
- Where spills occur, soak up liquid spillage with sand/sawdust and dispose of in a sensible manner. Do not permit run-off to sewer, storm water or open bodies of water

Full pails are HEAVY. Wear protective footwear and seek assistance if necessary.

FIRST AID MEASURES

Refer to **MSDS** for **Acryloc Ultra PSU** before use. For further information on Material Safety Data Sheets, call the Acryloc Tech – Info line on **1300 661 745** or visit **www.acryloc.com.au**

If swallowed, wash out mouth with water. Do **NOT** induce vomiting. Drink at least two (2) glasses of water. Seek medical attention.

Eye

Wash with copious amount of water for 15 minutes holding eyelid(s) open. Take care not to rinse contaminated water into non-affected eye. Seek medical attention.

Advice to Doctor

Treat symptomatically

MANUFACTURED BY:

Bizfine Pty Ltd

T/A Acryloc Building Products
174 Cavan Rd
DRY CREEK
South Australia 5094

P: +61 8 8368 0222

F: +61 8 8349 4260

E: sales@acryloc.com.au

W: www.acryloc.com.au